



# IntelliTouch Surface Wave

For High-Use Applications



### **Applications**

- Kiosks
- Ticketing machines
- Gaming machines
- Light industrial
- Office automation

Elo's IntelliTouch touchscreens, utilizing patented flat profile surface wave technology, are the picture-perfect, precision touch solution for highuse applications. The new flat profile technology has tiny transducers on the back of the touchscreen glass, eliminating the bumps on the front surface for a flatter integration solution. With the longest touchscreen warranty available, the IntelliTouch touchscreens are the preferred solution for applications requiring unsurpassed performance, reliability, and clarity. Their durable, pure-glass construction delivers the ultimate in image clarity and light transmission, preserves color purity, and works even if scratched. With their stable, drift-free operation, the IntelliTouch touchscreens guarantee a touch response that is on target. The IntelliTouch touchscreens are the ideal solution for kiosks, ticketing machines, gaming machines, light industrial, and office automation.

## **Benefits**

- Pure glass construction delivers the ultimate in image quality
- Stable, drift-free operation
- Continues to work even if scratched
- 10-year limited warranty






# **IntelliTouch Surface Wave Specifications**

### MECHANICAL

MECHANICAL	
Input Method	Finger or gloved hand (cloth, leather, or rubber) activation
Available Sizes*	10.4" to 30"; visit our Web site for full specifications and other offerings
ELECTRICAL	
Positional Accuracy	Standard deviation of error is less than 0.080 in. (2 mm)
Resolution	Touchpoint density is based on controller resolution of 4096 x 4096, plus 255 levels corresponding to touch pressure
Touch Activation Force	Typically 2 to 3 ounces (55 to 85 grams)
Controller	Board: Serial (RS232) or USB 1.1
OPTICAL	
Light Transmission	Up to 90% per ASTM D1003-92
ENVIRONMENTAL	
Temperature	Operating: -20°C to 50°C Storage: -40°C to 71°C
Relative Humidity	Operating: 40°C at 90% RH, noncondensing
Altitude	Operating: 10,000 ft (3,048 m)
	Storage/transport: 50,000 ft (15,240 m)
Chemical Resistance	The touch active area of the touchscreen is resistant to chemicals that do not affect glass, such as: acetone, toluene, methyl ethyl ketone, isopropyl alcohol, methyl alcohol, ethyl acetate, ammonia-based glass cleaners, gasoline, kerosene, vinegar
Electrostatic Protection	Per EN 61000-4-2, 1995: Meets Level 4 (15 kV air/8 kV contact discharges)
Agency Approvals	UL, cUL, TÜV, CE, FCC Class A
Sealability	Can be sealed to meet NEMA 3/3R/5/12/12K/13, IP64 standards
DURABILITY	
Surface Durability	Surface durability is that of glass, Mohs' hardness rating of 7
Expected Life	No known wear-out mechanism, as there are no layers, coatings, or moving parts. IntelliTouch technology has been operationally tested to more than 50 million touches in one location without failure, using a stylus similar to a finger.
Warranty	Touchscreen: 10-year limited warranty Controller: 5-year limited warranty

<sup>\*</sup>Available in most standard sizes. For some sizes, transducers are located on a beveled edge or the front of the glass. See the touchscreen component drawing for details.







Flat profile cable

Find out more about Elo's extensive range of touch solutions. Go to www.elotouch.com, or simply call the office nearest you.

**Corporate Headquarters** 

Elo TouchSystems 301 Constitution Drive Menlo Park, CA 94025-1110 800-ELO-TOUCH Tel 1-650-361-4700 Fax 1-650-361-4747 eloinfo@elotouch.com **Europe Headquarters**Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01

elosales@elotouch.com

Asia-Pacific Headquarters Tel +81 (45) 478-2161 Fax +81 (45) 478-2180 www.tps.co.jp Latin America Headquarters

Tel 1-305-428-5210 Fax 1-305-717-4909 www.elotouch.com.ar

Elo TouchSystems reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.